# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### 1 IDENTIFICATION OF THE SUBSTANCE/mixture AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Substance name: Oxalic acid
Synonyms: Ethanedioic acid

Chemical name and formula: Oxalic acid dihydrated— H<sub>2</sub>C<sub>2</sub>O<sub>4</sub>·2H<sub>2</sub>O

Trade name: Oxalic Acid
CAS: 6153-56-6
EINECS: 205-634-3
Molecular Weight: 126.07 g/mol

REACH Registration number: 01-2119534576-33-0000

1.2 Relevant identified uses of the substance or mixture and uses advised against

Please check the identified uses in table 1 of the Appendix of this SDS.

Uses advised against: There are no uses advised against.

1.3 Details of the supplier of the safety data sheet

Name: OXAQUIM, S.A.

Address: C/. Gregal, 3 – Urb. Parc Llevant – 43764 EL CATLLAR

(Spain)

Phone N°: +34 977 65 38 98 Fax N°: +34 977 65 39 30

E-mail of competent person responsible marcmiquel@oxaquim.com/agarvin@oxaquim.com

for SDS in the MS or in the EU:

1.4 Emergency telephone number

European Emergency N°: 112

National centre for Prevention and Treatment of 91 562 04 20

Intoxications N°:

Emergency telephone at the company +34 977 65 38 98

Available outside office 24 hours: ☐ Yes ☐ No

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### 2 HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance

# 2.1.1 Classification according to Regulation (EC) 1272/2008

Acute toxicity cat 4 oral and dermal Eye Damage 1

# 2.1.2 Classification according to Directive 67/548/EEC

Xn – harmful

#### 2.2 Label elements

# 2.2.1 Labelling according to Regulation (EC) 1272/2008

Signal word: Danger

#### Hazard pictogram:





#### Hazard statements:

H302: Harmful if swallowed.

H312: Harmful in contact with skin.
H318: Causes serious eye damage.

# Precautionary statements:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash thoroughly after handling.

P305 + P351 + P310: IF IN EYES: Rinse cautiously with water for several minutes. Immediately call

a POISON CENTER or doctor/physician.

P301 + P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

unwell.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P501: Dispose of contents/container to hazardous waste collection point.

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

# 2.2.2 Labelling according to Directive 67/548/EEC

# Indication of danger:

#### Xn harmful



# Risk phrases:

R21/22: Harmful in contact with skin and if swallowed.

R41: Risk of serious damage to eyes

# Safety phrases:

S2: Keep out of the reach of children S24/25: Avoid contact with skin and eyes.

# 2.3 Other hazards

The substance does not meet the criteria for PBT or vPvB substance. No other hazards identified.

# 3 COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 Substances

# Main constituent

Name: Oxalic acid dihydrated

CAS: 6153-56-6 EINECS: 205-634-3

# **Impurities**

No impurities relevant for classification and labelling

### 4 FIRST AID MEASURES

# 4.1 Description of first aid measures

# General advice

In case of loss of consciousness, never provide drink or induce vomiting.

#### Following inhalation

Move source of dust or move person to fresh air and rest.

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### Following skin contact

Carefully and gently brush the contaminated body surfaces in order to remove all traces of product for at least 15 minutes. Wash affected area immediately with plenty of water. Remove contaminated clothing. If necessary seek medical advice.

# Following eye contact

Rinse eyes immediately with plenty of water for at least 15 minutes and seek medical advice.

#### After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention.

## 4.2 Most important symptoms and effects, both acute and delayed

Prolonged or repeated skin contact may cause dermatitis. If inhaled can cause a burning sensation of nose and throat, coughing, shortness of breath, sore throat, symptoms of immediate effects.

4.3 Indication of any immediate medical attention and special treatment needed

Follow the advises given in section 4.1

#### 5 FIREFIGHTING MEASURES

# 5.1 Extinguishing media

# 5.1.1 Suitable extinguishing media

Use Water spray, powder, foam or carbon dioxide as extinguishing media. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### 5.1.2 Unsuitable extinguishing media

Avoid open flame. Avoid contact with oxidizing materials.

# 5.2 Special hazards arising from the substance or mixture

Keep away from sources of ignition. In case of fire toxic fumes may form CO, CO2.

# 5.3 Advice for fire fighters

The fire fighting equipment must use individual breathing equipment. In case of fire keep cool by spraying with water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### 6 ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

# 6.1.1 For non-emergency personnel

Ensure adequate ventilation.

Keep dust levels to a minimum.

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8).

#### 6.1.2 For emergency responders

Keep dust levels to a minimum.

Ensure adequate ventilation.

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8).

# 6.2 Environmental precautions

Contain the spillage. Keep the material dry if possible. Cover area if possible to avoid unnecessary dust hazard. Avoid uncontrolled spills to watercourses and drains. Any large spillage into watercourses must be alerted to the Environment Agency or other regulatory body.

# 6.3 Methods and material for containment and cleaning up

Collect up dry and deposit in waste containers for later disposal according to regulations. Wipe off with water. (Extra personal protection: P2 filter respirator for harmful particles).

#### 6.4 Reference to other sections

For more information on exposure controls/personal protection or disposal considerations, please check section 8 and 13 and the annex of this safety data sheet.

#### 7 HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Wear protective equipment (refer to section 8 of this safety data sheet). Do not wear contact lenses when handling this product. Keep dust levels to a minimum. Minimize dust generation. Enclose dust sources, use exhaust ventilation.

# 7.2 Conditions for safe storage, including any incompatibilities

The substance should be stored under dry conditions. Recipients tightly closed. Room temperature. Separated from strong bases, oxidizing materials, food and feed.

#### 7.3 Specific end use(s)

Please check the identified uses in table 1 of the Appendix of this SDS.

For more information please see the relevant exposure scenario, available via your supplier/given in the Appendix.

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

OEL (TWA): 1 mg/m3 (ACGIH 1990-1991).

OEL (como STEL): 2 mg/m3 (ACGIH 1990-1991).

DNEL for workers:

Local effects - acute: DNEL (derived not effect level) dermal: 0.69 mg / cm <sup>2</sup>

Systemic effects - long term: DNEL (derived not effect level) dermal: 2.29 mg / kg bw / day

Systemic effects - long term: DNEL (derived not effect level) inhalation: 4.03 mg / m³

DNEL for the general population:

Local effects - acute: DNEL (derived not effect level) Dermal: 0.35 mg / cm<sup>2</sup>

Systemic effects - long term: DNEL (derived not effect level) Dermal: 1.14 mg / kg bw / day

Systemic effects - long term: DNEL (derived not effect level) Oral: 1.14 mg / m³

PNEC water (freshwater): 0.1622 mg / L

PNEC water (sea water): 0.01622

PNEC water (intermittent spills): 1,622 mg / L

## 8.2 Exposure controls

To control potential exposures, generation of dust should be avoided. Further, appropriate protective equipment is recommended. Eye protection equipment (e.g. goggles or visors) must be worn, unless potential contact with the eye can be excluded by the nature and type of application (i.e. closed process). Additionally, face protection, protective clothing and safety shoes are required to be worn as appropriate.

Please check the relevant exposure scenario, given in the Appendix/available via your supplier.

# 8.2.1 Appropriate engineering controls

If user operations generate dust, use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne dust levels below recommended exposure limits.

#### 8.2.2 Individual protection measures, such as personal protective equipment

# 8.2.2.1 Eye/face protection

Do not wear contact lenses. Tight fitting goggles with side shields, or wide vision full goggles.

# 8.2.2.2 Skin protection

Dermal exposure should be minimized to the extent technically feasible. Wear suitable gloves (nitrile, neoprene, natural rubber, polyvinyl), standard work clothes, long pants, long sleeves, coveralls, closing with accessories and shoes openings resistant to corrosive chemicals and prevent penetration of dust.

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006,

# Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### 8.2.2.3 Respiratory protection

Local ventilation to keep levels below established threshold values is recommended. A suitable particle filter mask is recommended, depending on the expected exposure levels - please check the relevant exposure scenario, given in the Appendix/available via your supplier.

#### 8.2.2.4 Thermal hazards

The substance does not represent a thermal hazard, thus special consideration is not required.

#### 8.2.3 Environmental exposure controls

Avoid releasing to the environment.

Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority responsible for environmental protection or other regulatory body.

For detailed explanations of the risk management measures that adequately control exposure of the environment to the substance please check the relevant exposure scenario, available via your supplier.

For further detailed information, please check the Appendix of this SDS.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

Appearance: uncoloured crystals or white powder

Odour: odourless
Odour threshold: not applicable
pH: ~0,7(50g/l)

Melting point: not applicable (sublimes at >  $160 \,^{\circ}$ C) Boiling point: not applicable (sublimes at >  $160 \,^{\circ}$ C)

Flash point: not applicable Evaporation rate: not applicable

Flammability: non flammable (study result, EU A.10 method)

Explosive limits: non explosive (void of any chemical structures commonly

associated with explosive properties)

Vapour pressure: 0.0312 Pa at 25°C Vapour density: not applicable

Relative density: 0.813 (study result, EU A.3 method)
Solubility in water: 108 g/L at 25°C (study results)

Partition coefficient: - 1.7 at 23°C (study result, OECD Guideline 107)

Auto ignition temperature: no relative self-ignition temperature below 400 °C (study result, EU

A.16 method)

Decomposition temperature: > 160 °C
Viscosity: not applicable

Oxidising properties: no oxidising properties

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### 9.2 Other information

Not available

# 10 STABILITY AND REACTIVITY

#### 10.1 Reactivity

On contact with hot surfaces or flames this substance decomposes forming formic acid, carbon monoxide and carbon dioxide. The solution in water is a medium strong acid.

#### 10.2 Chemical stability

Under normal conditions of use and storage, oxalic acid is stable.

# 10.3 Possibility of hazardous reactions

Reacts violently with strong oxidants causing fire and explosion hazard. Reacts with some silver compounds to form explosive silver oxalate. Attacks some forms of plastic.

#### 10.4 Conditions to avoid

Minimise exposure to air and moisture to avoid degradation.

# 10.5 Incompatible materials

Alkaline solutions. Ammonia. Halogenates. Oxidizing agents. Metals. Water. / Heat.

# 10.6 Hazardous decomposition products

Formic acid. Carbon dioxide. Carbon monoxide.

# 11 TOXICOLOGICAL INFORMATION

# 11.1 Information on toxicological effects

Oxalic acid is classified as harmful by oral and dermal route and it entails a risk of serious damage to the eye.

#### 11.2 Toxicity endpoints and outcome of the effects assessment

**Absorption**: The primary health effect of oxalic acid is local irritation due to a pH shift. Therefore, absorption is not a relevant parameter for the effects assessment.

Acute toxicity: Oxalic acid is Oral and Dermal Acutely toxic cat. 4.

Oral: LD50 > 375 mg/kg bw (according to the method of Smyth, rat)

Dermal: LD50 > 20000 mg/kg bw (Pesticide Action Network, North America, rabbit)

Inhalation: no data available

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

Classification for acute toxicity is category 4 for oral and dermal route.

#### Irritation / corrosion

Eye irritation: Oxalic acid entails a risk of serious damage to the eye (OECD 405, rabbit).

Skin irritation: Oxalic acid is nor irritating to skin (OECD 404, rabbit).

Based on experimental results, oxalic acid requires classification as severely irritating to the eye [R41,

Risk of serious damage to eye; Eye Damage 1 (H318 - Causes serious eye damage)].

**Sensitisation**: Oxalic acid is not a skin sensitizer (OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay).

## Repeated dose toxicity

Toxicity of oxalic acid via the oral route is addressed by LOAEL of 150 mg/kg bw/day.

Toxicity of Oxalic acid via the dermal route is not considered as relevant in view of the anticipated insignificant absorption through skin.

Toxicity of Oxalic acid via inhalation is not considered as relevant.

Therefore, classification of Oxalic acid for toxicity upon prolonged exposure is not required.

# Mutagenicity

Bacterial reverse mutation assay (Ames test, OECD 471): Negative

Mammalian chromosome aberration test: Negative

Oxalic acid is void of any genotoxic potential.

Classification for genotoxicity is not warranted.

# Carcinogenicity

Oxalic acid is not considered as carcinogenic.

Human epidemiological data support lack of any carcinogenic potential of oxalic acid.

Classification for carcinogenicity is not warranted.

#### **Toxicity for reproduction**

Oxalic acid is not toxic to reproduction (experimental result, mouse).

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

12.1 Toxicity

Revision date: November / 2010

Printing Date: January 17, 2011

Human epidemiological data support lack of any potential for reproductive toxicity of oxalic acid. Classification for reproductive toxicity according to regulation (EC) 1272/2008 is not required.

12 ECOLOGICAL INFORMATION

12.1.1 Acute/Prolonged toxicity to fish

LC50 (96h) for freshwater fish: 160 mg/l (Deutsche Einheitsverfahren zur Wasser, Abwasser und Schlamm-Untersuchung)

12.1.2 Acute/Prolonged toxicity to aquatic invertebrates

EC50 (48h) for freshwater invertebrates: 162.2mg/l (OECD 202, Daphnia)

12.1.3 Acute/Prolonged toxicity to aquatic plants

Toxicity threshold (8 days) for freshwater algae: 80.0 mg/l

12.1.4Chronic toxicity to aquatic organisms

The long-term aquatic toxicity study on aquatic invertebrates shall be considered if the substance is poorly water soluble and oxalic acid is soluble in water. Also oxalic acid presents a low toxicity for the short term test.

12.1.5Toxicity to soil dwelling organisms

The oxalic acid is not supposed to be directly applied to soil and an indirect exposure to soil via sewage sludge transfer is unlikely since the substance is readily biodegradable. As oxalic acid is considered as "readily biodegradable", it can be assumed that it will be biodegraded within the STP process and as a consequence a transfer to the soil compartment is not expected. Therefore, no tests on terrestrial organisms are provided.

12.1.6Toxicity to terrestrial plants

EC50 (72 h) for terrestrial plants: 8 mM

12.1.7General effect

Oxalic acid has a low logKow and is readily biodegradable. The substance is not classified as hazardous for the environment.

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

# 12.2 Persistence and degradability

Oxalic acid is readily biodegradable, meeting the 10-d window. The biodegradation in seawater occurs at the same rate. Also the anaerobic biodegradation occurs rapidly.

#### 12.3 Bio accumulative potential

Not relevant for oxalic acid because this substance is ready biodegradable and highly soluble in water, and LogKow is negative.

## 12.4 Mobility in soil

Transport through the medium is rate-limiting. Degradation after 30 days at 20°C is up to 73% (based on CO2 evolution). Oxalic acid is easily biodegradable in soil.

#### 12.5 Results of PBT and vPvB assessment

The hazard assessment of oxalic acid reveals neither a need to classify the substance as dangerous to the environment, nor is it a PBT or vPvB substance, nor are there any further indications that the substance may be hazardous to the environment.

#### 12.6 Other adverse effects

No other adverse effects are identified

#### 13 DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Disposal of oxalic acid should be in accordance with local and national legislation. Processing, use or contamination of this product may change the waste management options. Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of container and unused contents in accordance with federal, state and local requirements. The used packing is only meant for packing this product. After usage, empty the packing completely.

# 14 TRANSPORT INFORMATION

Oxalic acid is not classified as hazardous for transport (ADR (Road), RID (Rail), IMDG / GGVSea (Sea).

#### 14.1 UN-Number

Not regulated

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### 14.2 UN proper shipping name

Not regulated

# 14.3 Transport hazard class(es)

Not regulated

# 14.4 Packing group

Not regulated

#### 14.5 Environmental hazards

None

#### 14.6 Special precautions for user

none

# 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## Not regulated

# 15 REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance

Authorisations: Not required

Restrictions on use: None

Other EU regulations: Oxalic acid is not a SEVESO substance, not an ozone depleting substance

and not a persistent organic pollutant.

National regulations: --

#### 15.2 Chemical safety assessment

A chemical safety assessment has been carried out for this substance.

#### 16 OTHER INFORMATION

Data are based on our latest knowledge but do not constitute a guarantee for any specific product features and do not establish a legally valid contractual relationship.

#### 16.1 Hazard Statement

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H318: Causes serious eye damage.

# prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

#### 16.2 Precautionary Statement

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash thoroughly after handling.

P305 + P351 + P310: IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTER or doctor/physician.

P301 + P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P501: Dispose of contents/container to hazardous waste collection point.

#### 16.3 Risk Phrases

R21/22: harmful in contact with skin and if swallowed

R41: risk of serious damage to eyes

#### 16.4 Safety Phrases

S2: Keep out of the reach of children

S24/25 - avoid contact with skin and eyes

#### 16.5 Abbreviations

EC<sub>50</sub>: median effective concentration LC<sub>50</sub>: median lethal concentration

LD<sub>50</sub>: median lethal dose

LOAEL: lowest observed adverse effect level

OEL: occupational exposure limit

PBT: persistent, bio accumulative, toxic chemical

PNEC: predicted no-effect concentration

STEL: short-term exposure limit TWA: time weighted average

vPvB: very persistent, very bio accumulative chemical

#### 16.6 Revision

The last revision (November 2010) has involved changes in all the sections, according to the new information obtained from the REACH dossier.

# <u>Disclaimer</u>

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006,

Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.1/EN

Revision date: November / 2010 Printing Date: January 17, 2011

appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.

#### **ANNEX**

Addition of exposure Scenarios as applicable

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

#### **APPENDIX: EXPOSURE SCENARIOS**

The current document includes all relevant occupational and environmental exposure scenarios (ES) for the production and use of oxalic acid as required under the REACH Regulation (Regulation (EC) No 1907/2006). For the development of the ES the Regulation and the relevant REACH Guidance have been considered. For the description of the covered uses and processes, the "R.12 – Use descriptor system" guidance (Version: 2, March 2010, ECHA-2010-G-05-EN), for the description and implementation of risk management measures (RMM) the "R.13 – Risk management measures" guidance (Version: 1.1, May 2008), for the occupational exposure estimation the "R.14 – Occupational exposure estimation" guidance (Version: 2, May 2010, ECHA-2010-G-09-EN) and for the actual environmental exposure assessment the "R.16 – Environmental Exposure Assessment" (Version: 2, May 2010, ECHA-10-G-06-EN) was used.

The exposure assessment of oxalic acid professional and industrial and consumer use is performed and organized based on several scenarios. An overview of the scenarios and the coverage of substance life cycle is presented in Table 1.

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

Table 1: Overview on exposure scenarios and coverage of substance life cycle

FC		ıre	Ide	entified (	uses	life o	ilting cycle ige					
ES numbe r	ES name	Manufacture	Formulation	End use	Consumer use	Service life for articles	Waste stage	Sector of use (SU)	Chemical product Category (PC)	Process Category (PROC)	Article category (AC)	ERC
	Industrial uses of aqueous solutions of oxalic acid	X	х	х				SU8, SU9, SU10, SU13, SU14, SU16, SU17, SU18,	PC0, PC7, PC9, PC10, PC14, PC 15, PC19, PC20, PC21, PC23, PC32, PC34 PC35, PC36, PC37	PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15		ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b
2	Industrial uses of solid oxalic acid	X	X	Х				SU8, SU9, SU10, SU13, SU14, SU16, SU17, SU18,	PC0, PC7, PC9, PC10, PC14, PC 15, PC19, PC20, PC21, PC23, PC32, PC34 PC35, PC36, PC37	PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC21, PROC22		ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b
	Professional uses of aqueous solutions of oxalic acid		Х	Х					PC9a, PC14, PC15, PC25. PC35, PC31	PROC10, PROC11, PROC15, PROC21		ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

ES numbe r	ES name	Manuf acture	Ide	ntified (	uses	life o	lting cycle ige	Sector of use (SU)	Chemical product Category (PC)	Process Category (PROC)	Article category (AC)	ERC
4	Professional uses of solid oxalic acid		X	х				SU22, SU6a, SU18		PROC10, PROC11, PROC15, PROC21		ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f
5	Consumer use of formulation containing Ox. Acc.			Х	Х			SU21	PC35, PC9a, PC31	PROC 21		ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

# 9.1. Industrial uses of aqueous solutions of oxalic acid

# 9.1.1. Exposure scenario

1. Title							
Free short t	itle	Use of aqueous solu	tions of oxalic acid				
ES number		1	1				
Systematic t use descript	itle based on or	PC0, PC7, PC9, PC1	SU3, SU5 SU6a, SU6b SU8, SU9, SU10, SU13, SU14, SU16, SU17, SU18, SU19, SU20, SU23, SU0 PC0, PC7, PC9, PC10, PC14, PC 15, PC19, PC20, PC21, PC23, PC32, PC35, PC36, PC37, PC34 ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b				
Processes, ta		Processes, tasks and	Processes, tasks and/or activities covered are described in Section 2 below.				
Assessment	Method	The assessment of ir	nhalation, dermal and environmental exposu	re and is base	ed on ECETOC TRA.		
2. Operation	nal conditions a	and risk management mea	sures				
PROC		REACH	definition		Involved tasks		
PROC1		Use in closed process, n	o likelihood of exposure				
PROC2	Use in c	closed, continuous process v	vith occasional controlled exposure				
PROC3		Use in closed batch process	s (synthesis or formulation)				
PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises						
PROC5	Mixing or blen	nding in batch processes for (multistage and/or s	formulation of preparations* and articles significant con-tact)	Further information is provided in the			
PROC7		Industrial	spraying				
PROC8a	Transfer of s	ubstance or preparation (cha containers at non-	arging/discharging) from/to vessels/large dedicated facilities	information	CHA Guidance on requirements and chemical afety assessment,		
PROC8b	Transfer of s		arging/discharging) from/to vessels/large dicated facilities	•	12: Use descriptor system 10-G-05-EN, 26/03/2010).		
PROC9	Transfer of s	ubstance or preparation into including	small containers (dedicated filling line, weighing)				
PROC10		Roller applicat	ion or brushing				
PROC13	Treatment of articles by dipping and pouring						
PROC15	Use as laboratory reagent						
ERC 1-6b	ERC 1-6b Manufacture, formulation and all types of industrial uses						
2.1 Control	of workers exp	osure					
Product cha	Г						
PROC Us		Used in preparation?	Content in preparation		Emission potential		

PROC	Used in preparation?	Content in preparation	Emission potential
PROC 7	Not excluded	> 25 % w/w (not restricted)	Medium
All other applicable PROCs	Not excluded	> 25 % w/w (not restricted)	Low

# Amounts used

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation, (industrial vs. professional) and level of containment/automation (as reflected in the PROC) is the main determinant of

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

. 1				
the	process	intrinsic	emission	potential.

#### Frequency and duration of use/exposure

All applicable PROCs > 4 hours (not restricted)

#### Technical conditions and measures at process level (source) to prevent release

Risk management measures at the process level (e.g. containment or segregation of the emission source) are generally not required in the processes.

#### Technical conditions and measures to control dispersion from source towards the worker

PROC	Level of separation	Localised controls (LC)	Efficiency of LC (according to ECTOC TRA)	Further information
All applicable PROCs	generally not required in the processes, unless a specific process step is conducted less than full-shift. If that is the case, it has to be guaranteed that the worker is	local exhaust ventilation (LEV)  (*The use of LEV is not mandatory for PROC1, PROC2 and PROC3, , but it is recommended)	N/A	

#### Organisational measures to prevent /limit releases, dispersion and exposure

Avoid inhalation or ingestion. General occupational hygiene measures are required to ensure a safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no eating and smoking at the workplace, the wearing of standard working clothes and shoes unless otherwise stated below. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home. Do not blow dust off with compressed air.

#### Conditions and measures related to personal protection, hygiene and health evaluation

	Specification of RPE and efficiency	•	Specification of eye protection	Further PPE
	protection with minimum efficiency 90%	(Nitrile, Neoprene, Natural rubber, Polyvinyl chloride,	to eyes, the use of face shield or eye protection is a	standard working clothes
All other applicable PROCS	Not required	natural rubber: Permeation Breakthrought > 360).	prerequisite for all process steps.	

# 2.2 Control of environmental exposure

#### Amounts used

The daily and annual amount per site (for point sources) is not considered to be the main determinant for environmental exposure.

#### Frequency and duration of use

Intermittent (< 12 time per year) or continuous use/release

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk management measures related to the environment aim to avoid discharging oxalic acid solutions into municipal wastewater or to surface water, in case such discharges are expected to cause significant pH changes. Regular control of the pH value during introduction into open waters is required. In general discharges should be carried out such that pH changes in receiving surface waters are minimised (e.g. through neutralisation).

#### Conditions and measures related to waste

Solid industrial waste of oxalic acid should be reused or discharged to the industrial wastewater and further neutralized if needed.

# 3. Exposure estimation and reference to its source

# Occupational exposure

ECTOC TRA was used for the inhalation and dermal exposure assessment. The risk characterisation ratio (RCR) for inhalation exposure is

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

based on the DNELinhalation for oxalic acid of 2.29 mg.kg<sup>-1</sup> day<sup>-1</sup>. The risk characterisation ratio (RCR) for dermal exposure is based on the DNELdermal for oxalic acid of 4.03 mg.kg<sup>-1</sup> day<sup>-1</sup>

PROC	Method used for inhalation exposure assessment	estimate exposure assess		Dermal exposure estimate mg/kg/day (RCR)	
PROC1	ECTOC TRA	0.038 (0.002)	ECTOC TRA	0.034 (0.009)	
PROC2	ECTOC TRA	0.375 (0.023)	ECTOC TRA	0.137 (0.034)	
PROC3	ECTOC TRA	1.125 (0.070)	ECTOC TRA	0.034 (0.009)	
PROC4	ECTOC TRA	1.876 (0.117)	ECTOC TRA	0.686 (0.170)	
PROC5	ECTOC TRA	1.876 (0.117)	ECTOC TRA	0.069 (0.017)	
PROC7	ECTOC TRA	1.876 (0.117)	ECTOC TRA	2.143 (0.532)	
PROC8a	ECTOC TRA	3.751 (0.234)	ECTOC TRA	0.137 (0.034)	
PROC8b	ECTOC TRA	0.563 (0.035)	ECTOC TRA	0.686 (0.170)	
PROC9	ECTOC TRA	1.876 (0.117)	ECTOC TRA	0.686 (0.170)	
PROC10	ECTOC TRA	3.751 (0.234)	ECTOC TRA	1.371 (0.340)	
PROC13	ECTOC TRA	3.751 (0.234)	ECTOC TRA	0.686 (0.170)	
PROC15	ECTOC TRA	1.876 (0.117)	ECTOC TRA	0.034 (0.085)	

# **Environmental exposure**

The environmental exposure assessment is only relevant for the aquatic environment, when applicable including STPs/WWTPs, as emissions of oxalic acid in the different life-cycle stages (production and use) mainly apply to (waste) water. The aquatic effect and risk assessment only deal with the effect on organisms/ecosystems due to possible pH changes related to H+ discharges, being the toxicity of oxalic acid expected to be negligible compared to the (potential) pH effect. Only the local scale is being addressed, including municipal sewage treatment plants (STPs) or industrial waste water treatment plants (WWTPs) when applicable, both for production and industrial use as any effects that might occur would be expected to take place on a local scale.

The high water solubility and very low vapour pressure indicate that oxalic acid will be found predominantly in water. Significant emissions or exposure to air are not expected due to the low vapour pressure. Significant emissions or exposure to the terrestrial environment are not expected either for this exposure scenario.

Environmental emissions	concentration ar effluent from ox	e production of oxalic acid can potentially result in an aquatic emission and locally increase the oxalic acid neentration and affect the pH in the aquatic environment. When the pH is not neutralised, the discharge of luent from oxalic acid production sites may impact the pH in the receiving water. The pH of effluents is rmally measured very frequently and can be neutralised easily as often required by national laws.					
Exposure concentration in waste water treatment	` ′	ERC2 (RCR)	ERC3 (RCR)	ERC4 (RCR)	ERC5 (RCR)	ERC6a (RCR)	ERC6b (RCR)
plant (WWTP) (RCR in STP)	0.024	0.001	0.08	0.10	0.10	0.016	0.01
Exposure concentration in aquatic pelagic compartment	When oxalic aci When oxalic aci water. The high	d is rejected to	surface water, th	e pH may decre	ase, depending		U U
Exposure concentration in sediments	The sediment co when oxalic acid					ed relevant for o particles is negl	
Exposure concentrations in soil and groundwater	The terrestrial correlevant.	The terrestrial compartment is not included in this exposure scenario, because it is not considered to be elevant.					
Exposure concentration in atmospheric	The air compart	ment is not incl	uded in this CSA	because it is co	nsidered not rel	evant for oxalic	acid.

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

compartment	
•	Bioaccumulation in organisms is not relevant for oxalic acid: a risk assessment for secondary poisoning is therefore not required.
chain (secondary poisoning)	

#### 4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Occupational

The DU works inside the boundaries set by the ES if either the proposed risk management measures as described above are met or the downstream user can demonstrate on his own that his operational conditions and implemented risk management measures are adequate. This has to be done by showing that they limit the inhalation and dermal exposure to a level below the respective DNEL (given that the processes and activities in question are covered by the PROCs listed above) as given below. If measured data are not available, the DU may make use of an appropriate scaling tool such as ECTOC TRA (www.ecetoc.org/tra) to estimate the associated exposure.

DNELinhalation for oxalic acid of 2.29 mg/(kg.day). DNELdermal for oxalic acid of 4.03 mg/(kg.day)

#### **Environmental**

If a site does not comply with the conditions stipulated in the safe use ES, it is recommended to apply a tiered approach to perform a more site-specific assessment.

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

# 9.2. Industrial uses of solid oxalic acid

# 9.2.1. Exposure scenario

1. Title							
Free short t	itle	Use of solid oxalic a	cid				
ES numer		2					
Systematic t use descript	itle based on or	PC0, PC7, PC9, PC	J6b SU8, SU9, SU10, SU13, SU14, SU16, 10, PC14, PC 15, PC19, PC20, PC21, PC23 3, ERC4, ERC5, ERC6a, ERC6b				
Processes, ta activities co		Processes, tasks and	or activities covered are described in Section	on 2 below.			
Assessment	Method	The assessment of in	nhalation, dermal and environmental exposu	re and is bas	ed on ECETOC TRA.		
2. Operation	nal conditions an	d risk management mea	sures				
PROC		REACH	definition		Involved tasks		
PROC1		Use in closed process, n	o likelihood of exposure				
PROC2	Use in clo	osed, continuous process v	with occasional controlled exposure				
PROC3	U	se in closed batch proces	s (synthesis or formulation)				
PROC4	Use in batch ar	nd other process (synthesi	s) where opportunity for exposure arises				
PROC5	Mixing or blend		formulation of preparations* and articles significant con-tact)				
PROC7	Industrial spraying						
PROC8a	Transfer of sub		arging/discharging) from/to vessels/large dedicated facilities	Further information is provided in the			
PROC8b	Transfer of sub		arging/discharging) from/to vessels/large dicated facilities	ECHA Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (ECHA-2010-G-05-EN, 26/03/2010).			
PROC9	Transfer of sub		small containers (dedicated filling line, weighing)				
PROC10		Roller applicat	ion or brushing				
PROC13		Treatment of articles b	y dipping and pouring				
PROC14	Production o		by tabletting, compression, extrusion, sation				
PROC15		Use as labor	atory reagent				
PROC21	Low energy	manipulation of substan	ces bound in materials and/or articles				
PROC22	Potentially closed processing operations with minerals/metals at elevated temperature						
ERC 1-6b	Manufacture, formulation and all types of industrial uses						
2.1 Control	of workers expos	sure					
Product cha	racteristics						
PR	OC	Used in preparation?	Content in preparation		Emission potential		
All applicabl	e PROCs No	ot excluded	(not restricted)		medium		
Amounts us	ed						

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation, (industrial vs. professional) and level of containment/automation (as reflected in the PROC) is the main determinant of the process intrinsic emission potential.

#### Frequency and duration of use/exposure

All applicable PROCs > 4 hours (not restricted)

#### Technical conditions and measures at process level (source) to prevent release

Risk management measures at the process level (e.g. containment or segregation of the emission source) are generally not required in the processes.

# Technical conditions and measures to control dispersion from source towards the worker

PROC	Level of separation	Localised controls (LC)	Efficiency of LC (according to ECTOC TRA)	Further information
	generally not required in the processes, unless a specific process step is conducted less than full-shift. If that is the case, it has to be guaranteed that the worker is separated from the emission	local exhaust ventilation (LEV)  (*The use of LEV is not mandatory for PROC1, PROC2, PROC3, PROC14, PROC15 and PROC21, but it is recommended)	N/A	-

## Organisational measures to prevent /limit releases, dispersion and exposure

Avoid inhalation or ingestion. General occupational hygiene measures are required to ensure a safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no eating and smoking at the workplace, the wearing of standard working clothes and shoes unless otherwise stated below. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home. Do not blow dust off with compressed air.

#### Conditions and measures related to personal protection, hygiene and health evaluation

PROC	Specification of RPE and efficiency		Specification of eye protection	Further PPE
All other applicable PROCS	,	(Nitrile, Neoprene, Natural rubber, Polyvinyl chloride, natural rubber: Permeation Breakthrought > 360).	to eyes, the use of face shield or eye protection is a	standard working clothes

#### 2.2 Control of environmental exposure

#### Amounts used

The daily and annual amount per site (for point sources) is not considered to be the main determinant for environmental exposure.

# Frequency and duration of use

Intermittent (< 12 time per year) or continuous use/release

# Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk management measures related to the environment aim to avoid discharging oxalic acid solutions into municipal wastewater or to surface water, in case such discharges are expected to cause significant pH changes. Regular control of the pH value during introduction into open waters is required. In general discharges should be carried out such that pH changes in receiving surface waters are minimised (e.g. through neutralisation).

# **Conditions and measures related to waste**

Solid industrial waste of oxalic acid should be reused or discharged to the industrial wastewater and further neutralized if needed.

#### 3. Exposure estimation and reference to its source

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

#### **Occupational exposure**

ECTOC TRA was used for the inhalation and dermal exposure assessment. The risk characterisation ratio (RCR) for inhalation exposure is based on the DNELinhalation for oxalic acid of 2.29 mg.kg<sup>-1</sup> day<sup>-1</sup>. The risk characterisation ratio (RCR) for dermal exposure is based on the DNELdermal for oxalic acid of 4.03 mg.kg<sup>-1</sup> day<sup>-1</sup>

PROC	Method used for inhalation exposure assessment	Inhalation exposure estimate mg/m3 (RCR)	Method used for dermal exposure assessment	Dermal exposure estimate mg/kg/day (RCR)	
PROC1	ECTOC TRA	0.010 (0.001)	ECTOC TRA	0.034 (0.009)	
PROC2	ECTOC TRA	0.100 (0.006)	ECTOC TRA	0.137 (0.034)	
PROC3	ECTOC TRA	0.100 (0.006)	ECTOC TRA	0.034 (0.009)	
PROC4	ECTOC TRA	2.500 (0.156)	ECTOC TRA	0.686 (0.170)	
PROC5	ECTOC TRA	2.500 (0.156)	ECTOC TRA	0.069 (0.017)	
PROC7	ECTOC TRA	5.000 (0.312)	ECTOC TRA	2.143 (0.532)	
PROC8a	ECTOC TRA	5.000 (0.312)	ECTOC TRA	0.137 (0.034)	
PROC8b	ECTOC TRA	1.250 (0.078)	ECTOC TRA	0.686 (0.170)	
PROC9	ECTOC TRA	2.000 (0.125)	ECTOC TRA	0.686 (0.170)	
PROC10	ECTOC TRA	1.000 (0.062)	ECTOC TRA	1.371 (0.340)	
PROC13	ECTOC TRA	0.500 (0.031)	ECTOC TRA	0.686 (0.170)	
PROC 14	ECTOC TRA	1.000 (0.062)	ECTOC TRA	0.343 (0.085)	
PROC15	ECTOC TRA	0.500 (0.031)	ECTOC TRA	0.034 (0.009)	
PROC21	ECTOC TRA	1.000 (0.062)	ECTOC TRA	0.283 (0.070)	
PROC 22	ECTOC TRA	0.100 (0.006)	ECTOC TRA	0.849 (0.211)	

# **Environmental exposure**

The environmental exposure assessment is only relevant for the aquatic environment, when applicable including STPs/WWTPs, as emissions of oxalic acid in the different life-cycle stages (production and use) mainly apply to (waste) water. The aquatic effect and risk assessment only deal with the effect on organisms/ecosystems due to possible pH changes related to H+ discharges, being the toxicity of oxalic acid expected to be negligible compared to the (potential) pH effect. Only the local scale is being addressed, including municipal sewage treatment plants (STPs) or industrial waste water treatment plants (WWTPs) when applicable, both for production and industrial use as any effects that might occur would be expected to take place on a local scale.

The high water solubility and very low vapour pressure indicate that oxalic acid will be found predominantly in water. Significant emissions or exposure to air are not expected due to the low vapour pressure. Significant emissions or exposure to the terrestrial environment are not expected either for this exposure scenario.

Environmental emissions	concentration ar effluent from ox	ne production of oxalic acid can potentially result in an aquatic emission and locally increase the oxalic acid incentration and affect the pH in the aquatic environment. When the pH is not neutralised, the discharge of a fluent from oxalic acid production sites may impact the pH in the receiving water. The pH of effluents is ormally measured very frequently and can be neutralised easily as often required by national laws.						
Exposure concentration in waste water treatment plant (WWTP) (RCR in STP)	0.024	0.001	0.0001	0.10	0.10	0.016	0.01	
in aquatic pelagic	When oxalic aci	nen oxalic acid is emitted to surface water, sorption to particulate matter and sediment will be negligible.  nen oxalic acid is rejected to surface water, the pH may decrease, depending on the buffer capacity of the ter. The higher the buffer capacity of the water, the lower the effect on pH will be.						

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

Exposure concentration in sediments	The sediment compartment is not included in this ES, because it is not considered relevant for oxalic acid: when oxalic acid is emitted to the aquatic compartment, sorption of to sediment particles is negligible.
•	The terrestrial compartment is not included in this exposure scenario, because it is not considered to be relevant.
Exposure concentration in atmospheric compartment	The air compartment is not included in this CSA because it is considered not relevant for oxalic acid.
*	Bioaccumulation in organisms is not relevant for oxalic acid: a risk assessment for secondary poisoning is therefore not required.

#### 4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Occupational

The DU works inside the boundaries set by the ES if either the proposed risk management measures as described above are met or the downstream user can demonstrate on his own that his operational conditions and implemented risk management measures are adequate. This has to be done by showing that they limit the inhalation and dermal exposure to a level below the respective DNEL (given that the processes and activities in question are covered by the PROCs listed above) as given below. If measured data are not available, the DU may make use of an appropriate scaling tool such as ECTOC TRA (www.ecetoc.org/tra) to estimate the associated exposure.

DNELinhalation for oxalic acid of 2.29 mg/(kg.day). DNELdermal for oxalic acid of 4.03 mg/(kg.day)

#### Environmental

If a site does not comply with the conditions stipulated in the safe use ES, it is recommended to apply a tiered approach to perform a more site-specific assessment.

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

# 9.3. Professional uses of aqueous solutions of oxalic acid

# 9.3.1. Exposure scenario

1. Title						
Free short title	Professional use of a	queous solutions of oxalic acid				
ES number	3					
Systematic title based on use descriptor	PROC10, PROC11,	SU22, SU6a, SU18 PC9a, PC14, PC15, PC25, PC35, PC31 PROC10, PROC11, PROC15, PROC21 ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f				
Processes, tasks and/or activities covered	Processes, tasks and	Processes, tasks and/or activities covered are described in Section 2 below.				
Assessment Method	The assessment of in	nhalation, dermal and environmental exposu	re and is base	ed on ECETOC TRA.		
2. Operational conditions	and risk management mea	sures				
PROC		REACH definition		Involved tasks		
PROC10	Roll	ler application or brushing	Further information is provided in the ECHA Guidance on information requirements and chemica safety assessment, Chapter R.12: Use descriptor system (ECHA-2010-G-05-EN, 26/03/2010)			
PROC11	1	Non industrial spraying				
PROC15	U	se as laboratory reagent				
PROC21	Low energy manip	oulation of substances bound in materials and/or articles				
ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f		oor and outdoor use of reactive substances cessing aids in open systems	(Echi 20	10 0 05 E11, 20/03/2010).		
2.1 Control of workers ex	posure					
<b>Product characteristics</b>						
PROC	Used in preparation?	Content in preparation		Emission potential		
PROC10, PROC11	Not excluded	Not excluded >25% w/w (not restricted)		High		
All other applicable PROCs	Not excluded	>25% w/w (not restricted)		Low		
Amounts used		ł				

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation, (industrial vs. professional) and level of containment/automation (as reflected in the PROC) is the main determinant of the process intrinsic emission potential.

#### Frequency and duration of use/exposure

All applicable PROCs > 4 hours (not restricted)

### Technical conditions and measures at process level (source) to prevent release

Risk management measures at the process level (e.g. containment or segregation of the emission source) are generally not required in the processes.

# Technical conditions and measures to control dispersion from source towards the worker

PROC	Level of separation	Localised controls (LC)	Efficiency of LC (according to ECTOC TRA)	Further information
**	Separation of workers is generally not required in the	local exhaust ventilation	N/A	

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

processes, unless a specific process step is conducted less than full-shift. If that is the case, it has to be guaranteed that the worker is separated from the emission	
source for the remaining shift.	

#### Organisational measures to prevent /limit releases, dispersion and exposure

Avoid inhalation or ingestion. General occupational hygiene measures are required to ensure a safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no eating and smoking at the workplace, the wearing of standard working clothes and shoes unless otherwise stated below. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home. Do not blow dust off with compressed air.

# Conditions and measures related to personal protection, hygiene and health evaluation

PROC	Specification of RPE and efficiency	Specification of gloves	Specification of eye protection	Further PPE
PROC10, PROC11	Use of respiratory protection with minimum efficiency of 90%	(Nitrile, Neoprene, Natural	As oxalic acid is irritating	
All other applicable PROCS	Not required	rubber Polyvinyl chloride	to eyes, the use of face shield or eye protection is a prerequisite for all process steps.	standard working clothes

# 2.2 Control of environmental exposure

#### Amounts used

1.000 kg/day

#### Frequency and duration of use

Intermittent (< 12 time per year) or continuous use/release

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk management measures related to the environment aim to avoid discharging oxalic acid solutions into municipal wastewater or to surface water.

# **Conditions and measures related to waste**

Oxalic acid wastes must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### 3. Exposure estimation and reference to its source

#### Occupational exposure

ECTOC TRA was used for the inhalation and dermal exposure assessment. The risk characterisation ratio (RCR) for inhalation exposure is based on the DNELinhalation for oxalic acid of 2.29 mg.kg<sup>-1</sup> day<sup>-1</sup>. The risk characterisation ratio (RCR) for dermal exposure is based on the DNELdermal for oxalic acid of 4.03 mg.kg<sup>-1</sup> day<sup>-1</sup>

PROC	Method used for	Inhalation exposure	Method used for dermal	Dermal exposure estimate
	inhalation	estimate	exposure assessment	mg/kg/day
	exposure assessment	mg/m3		(RCR)
		(RCR)		

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

PROC10	ECTOC TRA	1.876 (0.117)	ECTOC TRA	1.371 (0.340)
PROC11	ECTOC TRA	7.503 (0.468)	ECTOC TRA	2.143 (0.532)
PROC15	ECTOC TRA	3.751 (0.234)	ECTOC TRA	0.034 (0.009)
PROC21	ECTOC TRA	Only for solids	ECTOC TRA	0.283 (0.070)

#### **Environmental exposure**

The high water solubility and very low vapour pressure indicate that oxalic acid will be found predominantly in water. Significant emissions or exposure to air are not expected due to the low vapour pressure. Significant emissions or exposure to the terrestrial environment are not expected either for this exposure scenario.

<b>Environmental emissions</b>							
Exposure concentration	ERC8a (RCR)	ERC8b (RCR)	ERC8c (RCR)	ERC8d (RCR)	ERC8e (RCR)	ERC8f (RCR)	
in local fresh water	0.179	0.013	0.011	0.179	0.013	0.011	
in aquatic pelagic	When oxalic acid is emitted to surface water, sorption to particulate matter and sediment will be negligible.  When oxalic acid is rejected to surface water, the pH may decrease, depending on the buffer capacity of the water. The higher the buffer capacity of the water, the lower the effect on pH will be.						
•		The sediment compartment is not included in this ES, because it is not considered relevant for oxalic acid: when oxalic acid is emitted to the aquatic compartment, sorption of to sediment particles is negligible.					
Exposure concentrations in soil and groundwater	The terrestrial co	The terrestrial compartment is not included in this exposure scenario, because it is not considered to be relevant.					
Exposure concentration in atmospheric compartment	The air compartment is not included in this CSA because it is considered not relevant for oxalic acid.						
*		bioaccumulation in organisms is not relevant for oxalic acid: a risk assessment for secondary poisoning is nerefore not required.					

#### 4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

The DU works inside the boundaries set by the ES if either the proposed risk management measures as described above are met or the downstream user can demonstrate on his own that his operational conditions and implemented risk management measures are adequate. This has to be done by showing that they limit the inhalation and dermal exposure to a level below the respective DNEL (given that the processes and activities in question are covered by the PROCs listed above) as given below. If measured data are not available, the DU may make use of an appropriate scaling tool such as ECTOC TRA (www.ecetoc.org/tra) to estimate the associated exposure.

DNELinhalation for oxalic acid of 2.29 mg/(kg.day). DNELdermal for oxalic acid of 4.03 mg/(kg.day)

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

# 9.4. Professional uses of solid oxalic acid

# 9.4.1. Exposure scenario

1. Title							
Free short title	Professional use of s	olid oxalic acid					
ES number	4						
Systematic title based on use descriptor	PROC10, PROC11,	SU22, SU6a, SU18 PC9a, PC14, PC15, PC25, PC35, PC31 PROC10, PROC11, PROC15, PROC21 ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f					
Processes, tasks and/or activities covered	Processes, tasks and	Processes, tasks and/or activities covered are described in Section 2 below.					
Assessment Method	The assessment of in	halation, dermal and environmental exposu	re and is base	ed on ECETOC TRA.			
2. Operational conditions	2. Operational conditions and risk management measures						
PROC		REACH definition		Involved tasks			
PROC10	Roll	er application or brushing					
PROC11	1	Non industrial spraying	Further info	ormation is provided in the			
PROC15	U	se as laboratory reagent		CHA Guidance on requirements and chemical			
PROC21	Low energy manip	ulation of substances bound in materials and/or articles	safety assessment, Chapter R.12: Use descriptor system				
ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f	1	oor and outdoor use of reactive substances cessing aids in open systems	(ECHA-2010-G-05-EN, 26/03/2010).				
2.1 Control of workers ex	2.1 Control of workers exposure						
Product characteristics							
PROC	Used in preparation?	Content in preparation		Emission notential			

PROC	Used in preparation?	Content in preparation	Emission potential
All applicable PROCs	Not excluded	>25% w/w (not restricted)	Low

# Amounts used

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation, (industrial vs. professional) and level of containment/automation (as reflected in the PROC) is the main determinant of the process intrinsic emission potential.

#### Frequency and duration of use/exposure

All applicable PROCs > 4 hours (not restricted)

## Technical conditions and measures at process level (source) to prevent release

Risk management measures at the process level (e.g. containment or segregation of the emission source) are generally not required in the processes.

# Technical conditions and measures to control dispersion from source towards the worker

PROC	Level of separation	Localised controls (LC)	Efficiency of LC (according to ECTOC TRA)	Further information
	Separation of workers is generally not required in the processes, unless a specific process step is conducted	local exhaust ventilation	N/A	-

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

less than full-shift. I the case, it has to be guaranteed that the v separated from the e	vorker is	
source for the remai shift.	ning	

#### Organisational measures to prevent /limit releases, dispersion and exposure

Avoid inhalation or ingestion. General occupational hygiene measures are required to ensure a safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no eating and smoking at the workplace, the wearing of standard working clothes and shoes unless otherwise stated below. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home. Do not blow dust off with compressed air.

#### Conditions and measures related to personal protection, hygiene and health evaluation

PROC	Specification of RPE and efficiency	•	Specification of eye protection	Further PPE
All other applicable PROCS	Not required	(Nitrile, Neoprene, Natural rubber, Polyvinyl chloride, natural rubber: Permeation	As oxalic acid is irritating to eyes, the use of face shield or eye protection is a prerequisite for all process steps.	standard working clothes

#### 2.2 Control of environmental exposure

# **Amounts used**

1.000 kg/day

#### Frequency and duration of use

Intermittent (< 12 time per year) or continuous use/release

# Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk management measures related to the environment aim to avoid discharging oxalic acid solutions into municipal wastewater or to surface water.

#### Conditions and measures related to waste

Oxalic acid wastes must not be disposed together with household garbage. Do not allow product to reach sewage system.

### 3. Exposure estimation and reference to its source

#### **Occupational exposure**

ECTOC TRA was used for the inhalation and dermal exposure assessment. The risk characterisation ratio (RCR) for inhalation exposure is based on the DNELinhalation for oxalic acid of 2.29 mg.kg<sup>-1</sup> day<sup>-1</sup>. The risk characterisation ratio (RCR) for dermal exposure is based on the DNELdermal for oxalic acid of 4.03 mg.kg<sup>-1</sup> day<sup>-1</sup>

PROC	Method used for inhalation exposure assessment	Inhalation exposure estimate mg/m3 (RCR)	Method used for dermal exposure assessment	Dermal exposure estimate mg/kg/day (RCR)
PROC10	ECTOC TRA	0.100 (0.006)	ECTOC TRA	1.371 (0.340)
PROC11	ECTOC TRA	0.200 (0.012)	ECTOC TRA	2.143 (0.532)
PROC15	ECTOC TRA	0.020 (0.001)	ECTOC TRA	0.034 (0.009)
PROC21	ECTOC TRA	0.600 (0.037)	ECTOC TRA	0.283 (0.070)

#### **Environmental exposure**

The high water solubility and very low vapour pressure indicate that oxalic acid will be found predominantly in water. Significant emissions

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

or exposure to air are not expected due to the low vapour pressure. Significant emissions or exposure to the terrestrial environment are not
expected either for this exposure scenario.

- F						
<b>Environmental emissions</b>						
Exposure concentration	ERC8a (RCR)	ERC8b (RCR)	ERC8c (RCR)	ERC8d (RCR)	ERC8e (RCR)	ERC8f (RCR)
in local fresh water	0.179	0.013	0.011	0.179	0.013	0.011
Exposure concentration in aquatic pelagic compartment	When oxalic acid is emitted to surface water, sorption to particulate matter and sediment will be negligible.  When oxalic acid is rejected to surface water, the pH may decrease, depending on the buffer capacity of the water. The higher the buffer capacity of the water, the lower the effect on pH will be.					
Exposure concentration in sediments		The sediment compartment is not included in this ES, because it is not considered relevant for oxalic acid: when oxalic acid is emitted to the aquatic compartment, sorption of to sediment particles is negligible.				
Exposure concentrations in soil and groundwater	The terrestrial co	The terrestrial compartment is not included in this exposure scenario, because it is not considered to be relevant.				
Exposure concentration in atmospheric compartment	The air compartment is not included in this CSA because it is considered not relevant for oxalic acid.					
Exposure concentration relevant for the food chain (secondary poisoning)	Bioaccumulation therefore not req	-	ot relevant for oxa	lic acid: a risk asses	sment for secondary	poisoning is

# 4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

The DU works inside the boundaries set by the ES if either the proposed risk management measures as described above are met or the downstream user can demonstrate on his own that his operational conditions and implemented risk management measures are adequate. This has to be done by showing that they limit the inhalation and dermal exposure to a level below the respective DNEL (given that the processes and activities in question are covered by the PROCs listed above) as given below. If measured data are not available, the DU may make use of an appropriate scaling tool such as ECTOC TRA (www.ecetoc.org/tra) to estimate the associated exposure.

DNELinhalation for oxalic acid of 2.29 mg/(kg.day). DNELdermal for oxalic acid of 4.03 mg/(kg.day)

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 **Printing Date: November /2010** 

# 9.5. Consumer uses of oxalic acid

# 9.5.1. Exposure scenario

1. Title					
Free short title	Consumer uses of p	reparation containing oxalic acid			
ES number	5				
Systematic title based on use descriptor	SU21 PC9a, PC35, PC31 PROC21 ERC8a, ERC8b, ER	C8c, ERC8d, ERC8e, ERC8f			
Processes, tasks and/or activities covered	Processes, tasks and	Processes, tasks and/or activities covered are described in Section 2 below.			
Assessment Method	The assessment of ir	The assessment of inhalation, dermal and environmental exposure and is based on ECETOC TRA.			
2. Operational conditions	and risk management mea	sures			
PROC		REACH definition		Involved tasks	
PROC21	Low energy manip	oulation of substances bound in materials and/or articles	Further information is provided in the ECHA Guidance on information requirements and chemical control of the co		
ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f	*	oor and outdoor use of reactive substances cessing aids in open systems	safety assessment, Chapter R.12: Use descriptor system (ECHA-2010-G-05-EN, 26/03/2010).		
2.1 Control of exposure					
Product characteristics					
PROC	Used in preparation?	Content in preparation		Emission potential	
All applicable PROCs	Not excluded	>25% w/w (not restricted)		Low	

PROC	Used in preparation?	Content in preparation	Emission potential
All applicable PROCs	Not excluded	>25% w/w (not restricted)	Low

# **Amounts used**

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation, (and level of containment/automation (as reflected in the PC) is the main determinant of the use intrinsic emission potential.

# Frequency and duration of use/exposure

All applicable PROCs (not restricted)

# Technical conditions and measures at process level (source) to prevent release

Risk management measures for this consumer use are generally not required in the processes.

#### Conditions of use for the consumers

PC	PC sub-category	Product spray?	Amount of product used per application (g)	Product ingredient fraction by weight
PC35	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)	No	10	<5%
PC9a	Removers (paint-, glue-, wall paper-, sealant-remover)	No	10	<5%
PC31	Polishes and wax blends	No	10	<5%

# Organisational measures to prevent /limit releases, dispersion and exposure

Avoid inhalation or ingestion. General occupational hygiene measures are required to ensure a safe handling of the substance. These

prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010

Version: 1.0/EN

Revision date: November /2010 Printing Date: November /2010

measures involve good personal and housekeeping, no eating and smoking while using the substance. Do not wear contaminated clothing at home. Do not blow dust off with compressed air.

#### Conditions and measures related to personal protection, hygiene and health evaluation

	Specification of RPE and efficiency		Specification of eye protection	Further PPE
All other applicable PROCS	Not required	1	Not required Avoid contact with eyes	Not required

# 2.2 Control of environmental exposure

#### **Amounts used**

10 g/application

#### Frequency and duration of use

Intermittent (< 12 time per year)

#### 3. Exposure estimation and reference to its source

#### **Occupational exposure**

ECTOC TRA was used for the inhalation and dermal exposure assessment. The risk characterisation ratio (RCR) for inhalation exposure is based on the DNELdermal for consumer for oxalic acid of 1.14 mg.kg<sup>-1</sup> day<sup>-1</sup>.

PROC	Method used for inhalation exposure assessment	Inhalation exposure estimate mg/m3 (RCR)	Method used for dermal exposure assessment	Dermal exposure estimate mg/kg/day (RCR)
PC39	ECTOC TRA	0.02	ECTOC TRA	0.238 (0.20)
PC9a	ECTOC TRA	0.02	ECTOC TRA	0.238 (0.20)
PC31	ECTOC TRA	0.02	ECTOC TRA	0.238 (0.20)

#### **Environmental exposure**

The high water solubility and very low vapour pressure indicate that oxalic acid will be found predominantly in water. Significant emissions or exposure to air are not expected due to the low vapour pressure. Significant emissions or exposure to the terrestrial environment are not expected either for this exposure scenario.

<b>Environmental emissions</b>	
•	The sediment compartment is not included in this ES, because it is not considered relevant for oxalic acid: when oxalic acid is emitted to the aquatic compartment, sorption of to sediment particles is negligible.
Exposure concentrations in soil and groundwater	The terrestrial compartment is not included in this exposure scenario, because it is not considered to be relevant.
Exposure concentration in atmospheric compartment	The air compartment is not included in this CSA because it is considered not relevant for oxalic acid.
F	Bioaccumulation in organisms is not relevant for oxalic acid: a risk assessment for secondary poisoning is therefore not required.